SYMPHONY EVENTS & PRODUCTIONS BROCHURE 2024





AUDIO | LED SCREEN | LIGHTING | STAGE | TRUSS www.symphonydoha.com | info@symphonydoha.com | +974 50 333 686



SPEAKERS

Line array

RCF HDL 50 A

4400 Watt, 3 way amplification 140 dB max SPL 8 x high power neodymium transducers 48 kHz, 32 bit DSP processing RDNet on board Remote monitoring and control Symmetrical design Extremely low weight



EQUIPMENT CATALOUGE

- 1) Sound System
- 2) Lighting & Special Efx
- 3) Av
- 4) Trussing & Staging

Line array

ALL ALL

RCF HDL 30 A

2200W Two Way Amplifier 137 dB Max SPL 48 kHz, 32 bit DSP processing 1.4" Titanium Compression Driver 4-0" voice 2 x 10" Neodymium Woofers, 2.5" voice coil Exclusive FiRPHASE technology on-board RDNet Control and Management 680 Hz Crossover Point



SPEAKERS

Line array



RCF HDL 20 A

1400 Watt Peak power - 700 Watt RMS
135 dB max SPL
55 Hz 20 kHz frequency response
2 x 10" Woofers
1 x 3" Compression Driver
DSP controlled Input section with selectable presets
Tour grade safe and solid variable mechanics
Composite PP enclosure structurally wooden reinforced





SPEAKERS Sub Woofer

SUB 8006

5000 Watt Peak power - 2500 Watt RMS 141 dB max SPL 30 Hz - 120 Hz frequency response 2 x 18" Woofer DSP controlled Input section with selectable presets Delay control Integrated mechanics for multiple configuration with HDL 20-A Baltic birch tour grade cabinet

10 Nos

SPEAKERS Sub Woofer



HDL 18 AS

2000 Watt Peak Power - 1000 Watt Rms 1 X 18" Woofer 30 Hz - 140 Hz Frequency Response Dsp Controlled Input Section With Selectable Presets

4 Nos

SPEAKERS Sub Woofer



RCF

SUB 9007

7200 Watt Peak power - 3600 Watt RMS 141 dB max SPL 25 Hz - 120 Hz frequency response DSP controlled Input section with selectable presets Delay control Integrated mechanics for multiple configurations with HDL50-A, HDL20-A, HDL10-A RDNet remote and control Baltic birch tour grade cabinet

16 Nos





ART 715

FIRPhase technology 15" Woofer with 2.5" voice coil 1" Compression driver with 1.75" voice coil Power: 1400 W / peak, 700 W / RMS

4 Nos



SPEAKERS Active Full Range



ART 315/312

For Live Sound, Clubs, DJ Setups, Events 15" Woofer, 1" Compression Driver 800W Peak Class-D Digital Amplifier Frequency Response: 45 Hz to 20 kHz







SPEAKERS Active Wedge

SPEAKERS

Active Wedge

1100W Class-D amplifier

133 dB maximum SPL

directivity horn

12 Nos

NX 15 SMA

15" Neodymium Woofer 1" Kapton Dome Neodymium Tweeter 60 x 60° Dispersion 700W Digital Amplifier

Wide dispersion, 60 x 60° low distortion, & constant-

15" neo-coaxial woofer, 3.5"mm voice coil

8 Nos

TT 25 CXA







SPEAKERS Column Array



EVOX 8 ACTIVE TWO-WAY ARRAY

1400 WATT, 12" WOOFER, 2.5" V.C., 8 X 2" ULTRA COMPACT FULLRANGE, 1.0 V.C., 128 DB MAX SPL

4 Sets

SPEAKERS Column Array

EVOX 12 ACTIVE TWO-WAY ARRAY

1400 Watt 130 dB max SPL 40 Hz 20 kHz frequency response 15" Woofer 8 x 4" neodymium full-range woofer 90° x 30° slightly tilted pattern control Innovative DSP processing Pole mountable, easy set-up and transportation

2 Sets

SPEAKERS Passive Wedge



RCF

MAKPRO ST 15

S-152M is a two-way, full range stage monitor speaker system composed of one 15" woofer and one 3" titanium neodymium compression driver. It combines maximum internal enclosure volume with optimum presentation for near field stage monitor applications.

16 Nos



SPEAKERS Active Full Range



ART 912 Up to 130 dB Sound Pressure Level 2100W Class-D Bi-Amplification 50-20000 Hz linear frequency response 1.75" Compression Driver 12" Woofer

FiRPHASE zero degrees phase technology Bass Motion Control woofer excursion management









Mixing Consoles

Voi:

100

S6L-32D

Specification

128 input/64 outputs pro tools multi track recording/play back 1 Master Touchscreen, 3 Channel Touch Modules Faders 32 + 2

96 assignable knobs across 3 Channel Knob Modules Graphic TFTs with soft buttons; Touch and Turn assignable encoder; 2 assignable faders; monitoring, layout and snapshot controls; transport controls and function buttons 30-segment meters per channel, with pre- and post-fade metering options; Nominal indicator, Expander/Gate status and Compressor/Limiter gain reduction meters

- Frank







CONSOLES DIGITAL MIDAS PRO 2+DL251

Live Performance digital console control centre with up to 64 simultaneous input channels

8 award-winning Midas microphone preamplifiers

27 time-aligned and phase-coherent mix buses

AES50 networking allows up to 156 inputs and 164 outputs @ 96 kHz sample rate Touring grade road case featuring marine grade plywood, aluminium extrusions and composite density protective foam Advanced MCA (mix control association) channel control and navigation 8 VCA (variable control association) and 6 POPulation groups Up to 28 assignable 1/3 octave Klark Teknik DN370 graphic equalisers

1 Nos



MIDAS

MIDAS



CONSOLES DIGITAL **MIDAS M32+DL32**

32 award-winning Midas PRO microphone preamplifiers with switchable 48 V phantom power

16 electronically balanced low impedance line level outputs

ULTRANET personal monitoring system connectivity for in-ear applications

Digital audio and control connectivity for Turbosound speaker systems with ULTRANET networking capability

4 Nos







SOUNDCRAFT Si EXPRESSION 16

16 (24 - Si Expression 2, 32 - Si Expression 3) mono mic inputs 4 line inputs 66 inputs to mix 1 ViSi Connect[™] option card slot for 64 x 64 input/output expansion Freely assignable faders and patching

1 Nos

CONSOLES ANALOGUE



SOUND CRAFT MH4

Two fully modular frame sizes: 40+4 and 48+4 * Four full-function stereo mic/line inputs fitted as standard Flexible Auxiliary Bus structure allows use as FOH, Monitors or a combination

8 Group busses with 12 Aux busses in total (FOH mode) 16 Monitor busses: 16 mono, 12 mono + 2 stereo or 8 mono + 4 stereo (Monitor mode)

8 VCA groups and 8 Mute groups

Integral 20x8 Ouptut Matrix

LCR panning on inputs, Semi-parametric EQ on stereo Aux outputs

LED Input and VU Output metering

Snapshot automation and MIDI control

Integrated control of dbx DriveRack and BSS Varicurve Proven CPS800 Power Supply

1 Nos

CONSOLES ANALOGUE



MIDAS VENICE F 32

Live performance DIGI-LOG console with 32 input channels 24 mono and 4 stereo input channels with 16 award-winning Midas microphone preamplifiers

Industry acclaimed Midas XL3 4 band swept channel EQ 24 bit FireWire* audio interface with up to 32 inputs and 32 outputs



CONSOLES DIGITAL

MIDAS 132 R

16 award-winning Midas PRO microphone preamplifiers with switchable 48 V phantom power

16 electronically balanced low impedance line level outputs

ULTRANET personal monitoring system connectivity for in-ear applications

Digital audio and control connectivity for Turbosound speaker systems with ULTRANET networking capability

1 Nos



CONSOLES ANALOGUE



RCF

RCF E - SERIES

16-Channel Mixing Console With Superior Effects And Eqs

12 Mic/Line In, 2 Stereo Line In 4 Band Semiparametric Eq 6 Aux Sends Per Channel 32-Bit Floating-Point Z.core Dsp Effects Section

12Nos




CONSOLES ANALOGUE

RCF L PAD

12 Channel Mixing Console With Effects 6 Mono Input + 4 Stereo Input 4 Compressors (Ch. 1-4) Internal Digital Effects: 99 Preset Internal Psu 100V-240V, 50-60Hz, 40W









BACKLINE WIRELESS MICS

SHURE

SHURE

SHURE

SHURE ULX D

Available Transmitter Form factors: Bodypack, Desktop base, Boundary, Handheld Operating range (up to): 100 m (Under typical conditions) Extended 20 Hz - 20 KHz frequency range with totally flat response

8 Nos



SHURE QLX D

For Presenters and Performers WL185 Cardioid Lavalier Mic **Rugged Bodypack Transmitter** SM58 Dynamic Cardioid Mic/Transmitter

12 Nos



BACKLINE WIRELESS MICS

SHURE SLX D

Automatic Frequency Selection Automatic Transmitter Setup 960 Selectable frequencies across 24 MHzband width Detachable 1/4 wave antennas

24 Nos

BACKLINE WIRELESS MICS

SHURE BLX

Shure BLX® Wireless Systems combine professional-quality sound with simple setup and an intuitive interface for legendary audio performance right out of the box. Precision-built and available in a variety of configurations, it's the most accessible way to own the stage.

8 Nos





BACKLINE WIRELESS MICS

SHURE PG SERIES

For Presenters and Performers WL185 Cardioid Lavalier Mic Rugged Bodypack Transmitter SM58 Dynamic Cardioid Mic/Transmitter

10 Nos

BACKLINE WIRELESS IN EAR MONITORING



SHURE

SENNHEISER EW300G3

Sturdy metal housing (transmitter & receiver 42 MHz bandwidth: 1680 tunable UHF frequencies for interference-free reception

8 Nos

BACKLINE WIRELESS IN EAR MONITORING



SENNHEISER EW300G4

Sturdy metal housing (transmitter and receiver 42 MHz bandwidth: 1680 tunable UHF frequencies for interference-free reception

8 Nos

BACKLINE WIRELESS IN EAR MONITORING



SHURE PSM 200


Complete system consists of in-ear UHF transmitter, in-ear UHF pocket receiver and inear headphones













SHURE BETA 52

2 Nos





1 Nos



SENNHEISER DRUM KIT MIC

10 Nos







SENNHEISER E 835










DRUM KIT PEARL MASTERS

1 Set

<u>Pearl</u>









DRUMS Cymbals



K-Custom Dark

Dark Warm undertones with trashy dynamic reserves for accents 14" Hihat 14" 16" 18" Crash 20" Ride



01 Nos

DRUMS Shells and Hardware



Design Series

Gloss White 22" Kick, 10"/12"/16" Toms, 14" Share North American Hard Rock Maple DW 5000 Series Drum Hardware with Drum Throne DW 9000 series main rack package





DRUMS


54BIAN)

Cymbals

AAX O-Zone Crash

18" Multi-Hole O-Zone Design Thin and ultra-responsive Fine, clear and powerful sound at all volume levels





29 www.symphonydoha.com



DRUMS Zildjian

K-Custom 08" Dark Splash

Dark splash Traditional finish Played amongst others by Jimmy Branly, Gerry Brown, Loraine Faina and Steve Smith

01 Nos





Nano Mark 300

OUTPUT POWER: 300W RMS @ 4 ohm, 150W RMS @ 8 ohm INPUT: impedance 2 M ohm, max. voltage 15 V pp



01 Nos

BASS



Speaker Cabinet

Traveler 115P

1x 15" neodymium speaker Laterally adjustable piezo tweeter Power rating: 400 W Impedance: 8 Ohm Frequency range: 40-18000 Hz Ultra light and compact



01 Nos

GUITAR

Tube Amplifier



Hot Rod Deluxe IV

Hot Rod series 3 Channels: Normal, Drive and More Drive Power: 40 W Equipped with: 1x 12" Celestion A-Type Tubes: 3x 12AX7 and 2x 6L6 2 Jack inputs - input 2 with -6 dB







AMPS ROLAND D BASS

1 Set



AMPS MARSHALL MG 12 CX

1 Set



AMPS ROLAND JC 120 1 Set



AMPS MONTARBO MP6

1 Set



AMPS VOX AC 30



AMPS PEAVEY KB5



AMPS FENDER TWIN REVERB

1 Set



AMPS ROLAND KC 880




AMPS MARSHALL JVM 210 H + 1960 A 1 Set



AMPS AMPEG SVT 4 PRO + 810 E

1 Set



WYAMAHA

KEYBOARD Music Workstation

Motif XF7

76 FSX Keyboard (Initial Touch / Aftertouch) AWM2, with Expanded Articulation 16 Parts (internal), Audio Input Parts (A/D, FW*) *1 stereo Part Internal SDRAM: 128M 320 x 240 dot, 5.7-inch graphic colour backlit LCD



01 Nos

Pioneer Dj

DISC JOCKEY

Player

CDJ2000nxs2

DJ CD Player/Media Player with 7" Multicolour Touchscreen Complete rekordbox Integration - Black Extensive Media Format Support 4 Hot Cue Buttons Platter Controls Pro DJ Link enables even more features.



06 Nos

Pioneer Dj

DISC JOCKEY

Controller

XDJ-RX3

16 multicoloured pads for creative performance potential 10.1-inch touchscreen display offers awesome visual feedback for mixing and makes browsing quick and easy Nexus-style Quantize, Beat Sync, and Slip Mode provide let you effortlessly achieve polished results





Pioneer Dj


DISC JOCKEY

Mixer

DJM900nxs2

4-channel Digital DJ Mixer with Analog and Digital I/O.
3-band Switchable Iso EQs.
Dual USB Connectivity.
ProDJ Link - Black.
7 Sound Col FX.






PERCUSSION World Jam Block – Medium Pitch Modern versions of age-old wood blocks Crafted from Jenigor, LP's exclusive plastic formulation Rich sounds of wood blocks Strength and durability to withstand even the hardest-hitting players Heavy duty mounting bracket 01 Nos $(\mathbf{L}_{\mathbf{P}})$ PERCUSSION World Bar Chimes - Concert Series Chimes 36-bar Wooden bar, Aluminium alloy chimes Natural Wood, Polished chimes 01 Nos 0**BOSS** WIRELESS Instrument WL-20L For electric guitar & bass with low-impedance active pickups Newly developed BOSS technology for premium sound without interference Low latency (2.3 ms) and a range of up to 15 meters (with free visual contact) 01 Nos



42MHz bandwidth: 1680 tunable UHF frequencies for interference-free reception Enhanced frequency bank system with up to 16 compatible frequencies Adaptive diversity for high reception quality





27 Nos

Support depth: 28.5 cm 01 Nos



(horizontal) to 20°

with a third level

3/8" Thread connection

The top is also the basis for expanding





Memphis Pro Single

Particularly suitable for asymmetrical shapes

Height adjustable via elegant clamp lever

Torsion-proof extension tube and special rubber padding to protect guitar surface

















grandMA3



LIGHTING DESK **GRAND MA 3 FULL SIZE**

1 NOS



LIGHTING DESK GRAND MA 2 LIGHT

1 NOS

LIGHTING DESK **AVOLITES ARENA**

1 NOS

LIGHTING DESK **AVOLITE TIGER TOUCH 2**

4 NOS

LIGHTING DESK **AVOLITE TIGER TOUCH**

1 NOS

LIGHTING DESK CODE DMX CONTROLLER

1 NOS

LIGHTING DESK **AVOLITE PEARL 2008**

4 NOS



LIGHTING FIXTURES LED WASH XP 800

Power consumption:550W Input voltage: AC 110V-250V,50-60Hz Light source: Osram 15W RGBW LED X37pcs Lifetime: >100,000hours Electronic zoom range: 6°-50° Motor: Two speedy 3-phase motors for Pan/Tilt Pan/Tilt: 540°/310°



LIGHTING FIXTURES ROBE POINTE

LIGHT SOURCE Osram Sirius HRI 280W RO LIGHT OUTPUT Beam mode: 9.870 lm, 82.400 lx @ 20 m; Spot mode: 5.150 lm, 90.000 lx @ 5 m ZOOM RANGE 2,5° - 10° Beam mode, 5° - 20° Spot mode EFFECTS rotating and static gobo wheel, circular 8-facet and linear 6-facet prism

50 Nos



LIGHTING FIXTURES SPARKLY-WASH-37

Dimensions: 413 x 320 x 487mm Net weight: 17 Kg Color: Black IP rating: 20 Light source: 37 x 15 watts RGBW LED LED life expectancy: 50,000 Hrs Beam angle: 7° to 40° Light output: 11,000 Lux @ 10m @ 7°





LIGHTING FIXTURES GBR BATON

Color: RGBW 4in1 Color Mixing 2.Beam Angle:10°45° 60° optional 3.Dimmer: Electronic Linear Dimmer 0-100% 4.Strobe:Electronic Strobe 0-50HZ 5.DMX Channel:6/9/84/89 CH 6.Working Mode:Auto, DMX, Master-slave



LIGHTING FIXTURES XM LIGHT MEGA PLUS

Model: Mega Plus 382 Voltage: 110-240V,50/60Hz Bulb model: OSRAM SIRIUS HRI 382W Color wheel: 13+1 Power: 540 IP lever: 20 Size: 23KG Function: beam, spot, wash, zoom Carton size: 540x450x650 mm

60 Nos

LIGHTING FIXTURES ROBE 600 WASH

Light source 37x 10 W RGBW LED multichips Light output 4.820 lm, 3.340 lx @ 5 m Zoom range 15° - 60° Effects 3 LED rings control, rainbow effects, tungsten lamp effect, pre-programmed whites



LIGHTING FIXTURES LED BLINDER 4 WAY

LED System 4 x 80W (2 x 40W) Dual-White (1800K/3060K) COB Colour temperature 2490K Output 14000Im Refresh rate 3,1 Khz





LIGHTING FIXTURES LED BLINDER 2 WAY

LED System 2 x 80W (2 x 40W) Dual-White (1800K/3060K) COB Colour temperature 2490K Output 14000Im Refresh rate 3,1 Khz



LIGHTING FIXTURES CHAUVET LED PAR

• Light Source: 18 LEDs (quad-color RGBA) 7 W, (500 mA), 50,000 hours life expectancy

- Color Temperature (range): 2800 to 10000 K
- Installed Optics: 20°
- Beam Angle: 18°
- Field Angle: 32.5°
- Illuminance: 1,210 lux @ 5 m
- PWM Frequency: 600 Hz

100 Nos

LIGHTING FIXTURES

Light Source: LED Item Type: Wall Washers Input Voltage(V): AC90-240V;50-60Hz Lamp Luminous Flux(Im): 29160 Working Temperature:-25 - 45 Working Lifetime(Hour): 50000

130 Nos







GENERIC LIGHTS

100 NOS

GENERIC LIGHTS ETC SOURCE 4 PROFILE 20 NOS



GENERIC LIGHTS

26 NOS



GENERIC LIGHTS SKY BEAM 7000W

4 NOS



GENERIC LIGHTS 2K FRESNEL

24 NOS



GENERIC LIGHTS PAR 64

200 NOS



GENERIC LIGHTS MINI PAR 750







LIGHTING FIXTURES CHAUVET EZLINK PAR

100% TRUE wireless, battery-operated, quad-colour (RGBA) LED Par with built-in Bluetooth® wireless technology





GENERIC LIGHTS SELECON PROFILE





LIGHTS LED FESTOON HOLDER 250 mtr



GENERIC LIGHTS SELECON RAMA

GENERIC LIGHTS

DTS SCENA MINI SPOT

Power supply: 230 V 50/60 Hz

Lamp holder: GX 9.5 for 650 W or 1000 W lamps

Dimensions (L x W x H): 384 x 280 x 219 mm

Lens diameter: 150 mm Focus / Zoom: 12° - 53°

Weight: 5.5 kg 20 Nos

Beam angle range 6°-60° Lens diameter 110mm 4 1/4-inch Cable length 1m 3ft Colour frame size : 125mm x 125mm, 4 7/8" x 4 7/8" Accessories : 4-door barndoor / lens safety mesh / spare colour frame Weight2.8kg, 6lb 3oz Typical performance Spot 6°, Flood 60°, 72,500 cd, 7,500 cd, Field-14°, Field-70°

19 Nos

50 Nos

GENERIC LIGHTS SGM P5

- High-performance IP65 RGBW LED light source
- \cdot 43°, 21°, and 15° interchangeable lenses
- 20031 lumens in W
- \cdot DMX, RDM, and wireless control
- CTC control
- Accurate 16bit dimming performance
- Flicker-free / Programmable scenes

36 Nos



DIMMER PACK AVOLITE ART 9000 1 NOS







DMX SPLITER AVOLITE





DMX SPLITER CYCLOPS

5 NOS



DIMMER PACK AVOLITE ART CUBE










GENERIC

LED CURTAIN

6x4 mtr 4 NOS

LIGHTS





SPECIAL EFX DMX FAN

4 NOS



SPECIAL EFX DJ POWER SMOKE MACHINE

4 NOS



SPECIAL EFX DMX FIRE MACHINE

10 NOS



SPECIAL EFX SPARK MACHINE 25 NOS





LR 039s OUT DOOR LED SCREEN P3.9

Item LR 039S LED Type SMD Pixel Pitch (mm) 3.91 LED Density (pixel) 65536 Cabinet Resolution 128x128 /1 28x256 Scans 1/8 Brightness (nits) 4500 Refresh Rate (Hz) 3840 Contrast Ratio 5500:1 Color Gray Scale (level) 16bit Power Consumption (Max./Avg.) (W) 600/230 Viewing Angle (H/V) (°) 140/120 Cabinet Weight (kg) 7.5/13.5 Cabinet Material die-casting aluminum

800 Nos

AV

ΤV

LED SCREENS

PROJECTOR SCREENS

BARA (KEEKERAKEKE





ABSEN D4V OUT DOOR LED SCREEN P4.8

240 Nos



ABSEN D3 IN DOOR LED SCREEN P3.9

120 Nos



EPSON 6K PROJECTOR

2 Nos



PROCESSOR **NOVA STAR**

SWITCHER

MAGNIMAGE 780H

8 Nos

2 Nos

SONY

2 Nos

5K PROJECTOR



SWITCHER MAGNIMAGE 550

4 Nos





1 Nos



SHARP **3.5K PROJECTOR**

6 Nos



55″ 34 Nos



4 Nos







2 Nos





4 Nos




2 Nos




MEDIA SERVER RESOLUME







STAGE DECK 1.22 X 1.22Mtr, 1 - 1.5 Mtr 120 NOS





TRUSS 45x45 cm 168 Mtr






STAGE DECK 2 X 1Mtr, 0.6 - 0.8 Mtr 20 NOS






TRUSS 40x40 cm







1000 Mtr







TRUSS TOWER SYSTEM 75x65 cm

6 Nos



TRUSS BASE PLATE 50x50 cm

10 Nos



TRUSS TOWER SYSTEM 40x40 cm

8 Nos

10 Nos



TRUSS CORNER 40x40 cm 8 NOS



TRUSS CORNER 30x30 cm

36 NOS



ROOF TRUSS SYSTEM 15x8 Mtr


1 Nos



CIRCLE TRUSS 30x30 cm, 2Mtr Dia



TRUSS BASE PLATE 100x100 cm 36 Nos







16 NOS











)

FU




































www.symphonydoha.com info@symphonydoha.com | +974 50 333 686